

(a) Dataflow - $\mathbf{PP}_{AC}(\mathbf{V}_t \mathbf{F}_s \mathbf{N}_t, \mathbf{V}_s \mathbf{G}_s \mathbf{F}_t)$

```
for (v=0; v<V; v++) // temporal
  for (f=0; f<F; f++) // spatial
    for (n=0; n<N; n++) // temporal
      h[v][f] += x0[n][f]
```

```

1 for (v=0; v<V; v++) // spatial
1   for (g=0; g<G; g++) // spatial
1     for (f=0; f<F; f++) // temporal
1       x1[v][g] += h[v][f] * w[f][g]

```

Aggregation Dataflow: $V_t F_s N_t$

Combination Dataflow: V_s G_s F_t loaded from GB

Global Buffer

[illegible]
$$T_{V_{AGG}}=1, T_{N}=1, T_{F_{AGG}}=4 ; T_{V_{CMB}}=2, T_{G}=2, T_{F_{CMB}}=1$$

Global Buffer

(b) Dataflow -
SP_{AC} ($V_t F_s N_t, V_t F_s G_t$)

time

Space

$h[1][a]$ $h[1][b]$ $h[1][c]$ $h[1][d]$ $h[1][e]$ $h[1][f]$ $h[1][g]$ $h[1][h]$

$h[2][a]$ $h[2][b]$ $h[2][c]$ $h[2][d]$ $h[2][e]$ $h[2][f]$ $h[2][g]$ $h[2][h]$

$T V_{ACC}=1, T N=1, T F_{ACC}=8$

Aggregation dataflow is same as (a) except-

“h” is reused
within RF

time

$$T_{V_AGG}=1, T_{N}=1, T_{F_AGG}=8$$

Global Buffer

time ↓

$w[a][B]$ $w[b][B]$ $w[c][B]$ $w[d][B]$ $w[e][B]$ $w[f][B]$ $w[g][B]$ $w[h][B]$

$w[a][A]$ $w[b][A]$ $w[c][A]$ $w[d][A]$ $w[e][A]$ $w[f][A]$ $w[g][A]$ $w[h][A]$

$h[1][a]$ $h[1][b]$ $h[1][c]$ $h[1][d]$ $h[1][e]$ $h[1][f]$ $h[1][g]$ $h[1][h]$

Spatial reuse and spatial reduction of partial sums of output matrix: Spatially mapped F

$x^1[1][B]$ $x^1[1][A]$

* these could also be partial sums if $F > \text{num_PE}$

time →

```
for (v=0; v<V; v++) // temporal
  for (f=0; f<F; f++) // spatial
    for (g=0; g<G; g++) // temporal
      x1[v][g] += h[v][f] * wf[f][g]
```

Combination Dataflow:
 $V_t F_s G_t$

Spatial reuse and spatial reduction of partial sums of output
matrix. Spatially mapped F

$x^1[1][B]$ $x^1[1][A]$ * these could also be partial sums if $F > \text{num PEs}$

$$T_{V_{CMB}}=1, T_G=1, T_{F_{CMB}}=8$$

PEs whose
Dataflow is
shown